




U7 Pro XG

U7-Pro-XG-B



Overview

Dimensions	Ø206 x 32.5 mm (Ø8.1 x 1.3")
WiFi Standard	WiFi 7
Spatial Streams	6
Coverage Area	140 m ² (1,500 ft ²)
Max. Client Count	300+
Uplink	10 GbE
Mounting	Ceiling, Wall (Lite Mount Included)
Power Method	PoE+

Performance

MIMO

6 GHz	2 x 2 (DL/UL MU-MIMO)
5 GHz	2 x 2 (DL/UL MU-MIMO)
2.4 GHz	2 x 2 (DL/UL MU-MIMO)
Max. Data Rate	
6 GHz	5.8Gbps (BW320)
5 GHz	4.3 Gbps (BW240)
2.4 GHz	688 Mbps (BW40)
Antenna Gain	
6 GHz	6dBi
5 GHz	5 dBi
2.4 GHz	4 dBi
Max. TX Power	
6 GHz	24 dBm
5 GHz	26 dBm
2.4 GHz	23 dBm
Max. BSSIDs	8 per Radio
Supported Data Rates	
802.11be (WiFi 7)	6 GHz: 7.3 Mbps to 5.8 Gbps (MCS0 - MCS13 NSS1/2, EHT 20/40/80/160/320) 5 GHz: 7.3 Mbps to 4.3 Gbps (MCS0 - MCS13 NSS1/2/3/4, EHT 20/40/80/160/240)
802.11ax (WiFi 6)	7.3 Mbps to 2.4 Gbps (MCS0 - MCS11 NSS1/2, HE 20/40/80/160)
802.11ac (WiFi 5)	6.5 Mbps to 1.7 Gbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80/160) 4 dBi
802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)

Features

Wireless Meshing	✓
Band Steering	✓
802.11v BSS Transition Management	✓
802.11r Fast Roaming	✓
802.11k Radio Resource Management (RRM)	✓
Advanced Radio Management	✓
Passpoint (Hotspot 2.0)	✓
Captive Hotspot Portal	✓
Custom Branding Landing Page	✓
Voucher Authentication	✓
Payment-Based Authentication	✓
External Portal Server Support	✓
Password Authentication	✓
Guest Network Isolation	✓
Private Pre-Shared Key (PPSK)	✓
WiFi Speed Limiting	✓
Client Device Isolation	✓
WiFi Schedules	✓
RADIUS over TLS (RadSec)	✓
Dynamic RADIUS-assigned VLAN	✓

Max. Power Consumption	22W
Supported Voltage Range	42.5—57V DC
Networking Interface	(1) 10 GbE RJ45 port
Weight	750 g (1.7 lb)
Management	Ethernet
Enclosure Material	UV-stabilized polycarbonate, aluminum alloy
Mount Material	Stainless steel (SUS304), galvanized steel (SGCC)
LEDs	
System	White/Blue
Channel Bandwidth	HT 20/40, VHT 20/40/80/160, HE 20/40/80/160, EHT 20/40/80/160/240/320 (MHz)
NDA Compliant	✓
Certifications	CE, FCC, IC
Ambient Operating Temperature	-30 to 40° C (-22 to 104° F)
Ambient Operating Humidity	5 to 95% noncondensing

Software

Application Requirements

UniFi Network	Version 9.0.114 and later (U7 Pro XG - White) Version 9.1.120 and later (U7 Pro XG - Black)
---------------	--