



AI Port

UP-AI-PORT



*PoE+ input required for PoE output (12.95W), PoE++ input required for PoE+ output (25.5W).
**Rack mount sold separately.
*** SD card support coming soon.

^ Overview

Dimensions

Without mount: 150 x 64 x 38.4 mm (5.9 x 2.5 x 1.5")
With mount: 152.7 x 69 x 47.8 mm (6 x 2.7 x 1.9")

Resolution

Max. camera resolution:
Width: 3840 pixels
Height: 2160 pixels

Networking Interface

(1) GbE RJ45 port

^ Hardware

Power Method

PoE
PoE+ input required for PoE output (12.95W)
PoE++ input required for PoE+ output (25.5W)

Pole Mount Diameter

>45 mm (1.8") on pipe outer diameter

Weight

Without mount: 258.3 g (9.1 oz)
With mount: 294 g (10.4 oz)

Enclosure Material

Polycarbonate

Button

Factory-reset

Ambient Operating Temperature

-20 to 40° C (-4 to 104° F)

Ambient Operating Humidity

20 to 90% noncondensing

NDAA Compliant

✓

Certifications

FCC, IC, CE

^ **Software**

Application Requirements

Web Application

UniFi Protect: Version 5.1 and later

Mobile App

UniFi Protect iOS™ and Android™