




Flex Mini 2.5G

USW-5FLEX-2.5G



*Optional powering with included 5V, 1A USB-C adapter

Mechanical

Dimensions	117.1 x 90 x 21.2 mm (4.6 x 3.5 x 0.8")
Weight	206 g (7.3 oz)
Enclosure material	Polycarbonate

Hardware

Management interface	Ethernet In-Band
Networking interface	(5) 1/2.5 GbE RJ45 ports
Total non-blocking throughput	12.5 Gbps
Switching capacity	25 Gbps
Forwarding rate	18.6 Mpps
Power method	(1) AC power adapter, 5V DC, 1A (1) PoE (PairA 1, 2+; 3, 6-)(PairB 4, 5+; 7, 8-)
Power supply	External AC/DC adapter UniFi PoE switch
Supported voltage range	AC/DC input: 5V DC PoE input: 44—57V DC
Max. power consumption	AC/DC input: 5W PoE input: 6.4W

Button	Factory reset
Ambient operating temperature	-20 to 45° C (-4 to 113° F)
Ambient operating humidity	10 to 90% noncondensing
Certifications	CE, FCC, IC

Switching Features

Layer 2 features	STP / RSTP with priorities and port-level disable Port isolation Storm control Port mirroring Multicast / broadcast rate limiting Flow control Jumbo frames Egress rate limit Proprietary loop protection
Layer 3 features	-

LEDs

System	(1) Blue/white: power Blinking white: bootup in progress Blinking blue: firmware upgrading Steady white: factory defaults; unit is awaiting adoption Steady blue: unit is adopted
Ethernet	(5) Green: link/activity

Application Requirements

UniFi Network	Version 8.4.62 and later
----------------------	--------------------------