



# Flex Mini

## USW-Flex-Mini



\*Single-unit packages include the 5V, 1A USB-C power adapter

<b>Dimensions</b>	107 x 70 x 21 mm (4.2 x 2.8 x 0.8")
<b>Weight</b>	150 g (5.3 oz)
<b>Enclosure material</b>	Polycarbonate
<b>Hardware</b>	
<b>Management interface</b>	Ethernet In-Band
<b>Networking interface</b>	(5) GbE RJ45 ports
<b>Total non-blocking throughput</b>	5 Gbps
<b>Switching capacity</b>	10 Gbps
<b>Forwarding rate</b>	7.44 Mpps
<b>Power method</b>	(1) USB Type C, 5V (1) PoE/PoE+, 44—57V DC, 0.05—0.04A
<b>Power supply</b>	5V, 1A power adapter* *Only single-unit packages include the 5V, 1A USB-C power adapter.
<b>Supported voltage range</b>	USB Type C: 4.7—5.3V DC PoE/PoE+: 44—57V DC
<b>Max. power consumption</b>	2.5W
<b>ESD/EMP protection</b>	Air: ± 16kV, contact: ± 12kV
<b>Button</b>	Factory reset
<b>Ambient operating temperature</b>	-5 to 45° C (23 to 113° F)
<b>Ambient operating humidity</b>	10 to 90% noncondensing
<b>Certifications</b>	CE, FCC, IC

## Switching Features

### Layer 2 features

Port isolation  
Storm control  
Port mirroring  
Multicast / broadcast rate limiting  
Flow control  
Jumbo frames  
Egress rate limit

### Layer 3 features LEDs

–

### System

Status

### Ethernet

Speed/link/activity

## Application Requirements

### UniFi Network

Version 5.12.5 and later