



Doorbell Lite

UVC-Doorbell-B



Overview

Dimensions	137 x 40 x 26.4 mm (5.4 x 1.6 x 1")
IR Night Vision	5 m (16 ft)
Smart Detections (People, Vehicles, Animals)	✓
Resolution	5MP
Field of View	H: 95.8°, V: 131.2°, D: 175.9°
Audio	Two-way audio
Weatherproofing	IPX5
Mounting	Wall, 20° wedge (Included) Gang box, junction box (Optional)

Performance

Networking Interface	10/100 MbE port
Video	
<ul style="list-style-type: none">• Image Settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay
<ul style="list-style-type: none">• Max. Frame Rate	24 FPS
<ul style="list-style-type: none">• Resolution	5MP 1920 x 2560 (3:4)
Optics	
<ul style="list-style-type: none">• Sensor	1/2.7" 5MP
<ul style="list-style-type: none">• Lens	Fixed focal length
<ul style="list-style-type: none">• Night Mode	Built-in IR LED illumination and IR cut filter

Hardware

Max. Power Consumption	8W
Supported Voltage Range	37–57V DC
Power Method	PoE
Processor	Dual-core Arm® Cortex®-A7 based chip
Weight	Device: 142 g (5 oz) With flat wall mount: 165 g (5.8 oz) With 20° wedge mount: 179 g (6.3 oz)
Enclosure Material	Polycarbonate, metal
Mount Material	Formed sheet metal
Button	(1) Ring button (1) Factory-reset
Ambient Operating Temperature	-30 to 50° C (-22 to 122° F)

Ambient Operating Humidity	20 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC

For more information about this product or other Ubiquiti products, please visit: <https://techspecs.ui.com>