



# G5 Dome Ultra

## UVC-G5-Dome-Ultra



### Mechanical

**Dimensions** Ø63.6 x 68.2 mm (Ø2.5 x 2.7")

**Weight** 175 g (6.2 oz)

**Enclosure material** Aluminum alloy, polycarbonate

**Mount material** Stainless steel

**Resistance** IK06

### Optics

**Sensor** 1/2.4" CMOS

**Lens** Fixed focal length

**View angle** H: 102.4°, V: 54.9°, D: 120.6°

**Night mode** Built-in IR LED illumination and IR cut filter

**IR distance** 20 m (65 ft)

## Video

### Resolution

4MP 2688 x 1512 (16:9)

### Max. frame rate

30 FPS

### Image settings

Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay

## System

### Processor

Dual-core Arm® Cortex®-A7 based chip

### Networking interface

10/100 MbE RJ45 port

### Max. power consumption

4.2W

### Power method

PoE

### Supported voltage range

37–57V DC

### Button

Factory reset

### Mounting

Surface mount

### Ambient operating temperature

-20 to 40° C (-4 to 104° F)

### Ambient operating humidity

10 to 90% noncondensing

### Certifications

FCC, IC, CE

## Software

### Web application

UniFi Protect

### Mobile app

UniFi Protect iOS™ and Android™